Product sheet

Subminiature connector



Product Pole


Contacts: 5, Female cable connector with


strain relief

Area Article number

Snap-in IP40 Series 719 09 9790 71 05







You can find the item description on the next page.

Technical data

Common values

Connector Design Connector locking system Termination Wire gauge (mm) Wire gauge (AWG) Cable outlet

Upper temperature Lower temperature

Cable data

material housing Insulation single lead Single lead structure Conductor resistance Female cable connector Snap

Solder 0.25 mm² 24 max. 5 mm 70 °C

-25 °C

Electrical values

Rated voltage 60 V Rated impulse voltage 800 V Pollution degree Overvoltage category Ш Material group Ш Rated current (40°C) 3 A Volume resistivity ≤ 3 mΩ EMV compliance not shieldable Degree of protection IP40 Mechanical operation > 100 mating cycles

Material

Material of contact CuSn (Bronze) Contact plating Au (Gold) Material of contact body Material of housing PA

Contacts: 5, Female cable connector with strain relief, max. cable outlet 5 mm

Product sheet

Subminiature connector



Product

Pole

Contacts: 5, Female cable connector with

strain relief 5

Area Article number

Snap-in IP40 Series 719 09 9790 71 05

Item description Druckschraube pressing screw Buchseneinsatz female insert Klemmkorb Steckereinsatz pinch ring male insert