

# Product data sheet

## Binder connectors

### Male panel mount connector




## Solder

UL-approval

09 0453 00 14

<https://www.ac-solutions.be/en/product/0904530014>



## Specifications

### General Characteristics

|                    |                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------|
| Screw size         | M16                                                                                       |
| Series             | Miniature                                                                                 |
| Subseries          | 423-723-425                                                                               |
| Gender             | Male                                                                                      |
| Number of contacts | 14                                                                                        |
| Contact terminal   | Solder                                                                                    |
| Upper temperature  | +95 °C                                                                                    |
| Lower temperature  | -40 °C                                                                                    |
| Protection degree  | IP67                                                                                      |
| Locking system     | Screw (M16)                                                                               |
| Mating cycles      | >500                                                                                      |
| Connector Diameter | 20 mm                                                                                     |
| Wire-section       | 0.25 mm²                                                                                  |
| Remark*            | *In case of pollution degree 2, overvoltage category II rated voltage is reduced to 32 V. |

# Product data sheet

## Binder connectors

### Male panel mount connector



## Electrical parameters

|                         |           |
|-------------------------|-----------|
| Nominal current         | 3 A       |
| Nominal voltage         | 60 (32) V |
| Impuls voltage          | 500 V     |
| Max. contact resistance | 3 m?      |
| Pollution degree        | 1 (2)*    |
| Overvoltage categorie   | I (II)*   |

## Material

|                     |                               |
|---------------------|-------------------------------|
| Material group      | III                           |
| Material of insert  | PBT (UL 94 V-0)               |
| Material of housing | Zinc diecasting nickel plated |
| Material of contact | CuZn (Brass)                  |
| Plating             | Au (Gold)                     |