

# Product data sheet

## Binder connectors


### Female panel mount connector



## IP40

09 4832 25 08

<https://www.ac-solutions.be/en/product/0948322508>



## Specifications

### General Characteristics

|                    |                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------|
| Series             | Miniature                                                                                 |
| Subseries          | 440                                                                                       |
| Gender             | Female                                                                                    |
| Number of contacts | 8                                                                                         |
| Contact terminal   | Solder                                                                                    |
| Upper temperature  | +85 °C                                                                                    |
| Lower temperature  | -40 °C                                                                                    |
| Protection degree  | IP40                                                                                      |
| Locking system     | Push-Pull                                                                                 |
| Mating cycles      | >1000                                                                                     |
| Connector Diameter | 25 mm                                                                                     |
| Wire-section       | 0.75 mm <sup>2</sup>                                                                      |
| Remark*            | *In case of pollution degree 2, overvoltage category II rated voltage is reduced to 32 V. |

### Electrical parameters

# Product data sheet

## Binder connectors

### Female panel mount connector



|                         |           |
|-------------------------|-----------|
| Nominal current         | 5 A       |
| Nominal voltage         | 60 (32) V |
| Impuls voltage          | 500 V     |
| Max. contact resistance | 3 m?      |
| Pollution degree        | 1 (2)*    |
| Overvoltage categorie   | I (II)*   |

## Material

|                     |                            |
|---------------------|----------------------------|
| Material group      | III                        |
| Material of insert  | PBT (UL 94 V-0)            |
| Material of housing | CuZn (Brass nickel plated) |
| Material of contact | CuSn (Bronze)              |
| Plating             | Au (Gold)                  |