

Product data sheet

Hummel connectors



Straight Connector, Female Thread



2+3+PE, insert for sockets, power

7.710.823.000

<https://www.ac-solutions.be/en/product/7710823000>



Specifications

General Characteristics

Number of contacts	6 mixed layout
Gender of required insert	Female
Upper temperature	125 °C
Lower temperature	-40 °C
Connector locking system	Screw
Protection degree	IP67/IP69K
Mating cycles	>500
Terminal type	Crimp
Cable diameter	21-28 mm
Wire section (a)	1-4 mm
Wire section (b)	1,5-16 mm
Crimp contacts (to be ordered separately)	2x2mm & 4x3,6mm
Contact diameter (a)	2
Contact diameter (b)	3.6

Electrical parameters

Product data sheet

Hummel connectors

Straight Connector, Female Thread



Nominal current (a)	28 A
Nominal current (b)	55 A
Insulation resistance	> 10 ¹³
Nominal voltage (degree of pollution 3) (a)	300 V
Nominal voltage (degree of pollution 3) (b)	600 V
Test voltage (a)	2500 V
Test voltage (b)	4000 V
Max. contact resistance (a)	3 m?
Max. contact resistance (b)	1 m?

Material

Housing material	Copper-Zinc alloy/ Die casting
Housing plating	Nickel plated