

# Product data sheet


## Binder connectors

### Male angled connector



77 1427 0000 50003 0200

<https://www.ac-solutions.be/en/product/7714270000500030200>



## Specifications

### General Characteristics

|                    |                     |
|--------------------|---------------------|
| Screw size         | 7/8                 |
| Series             | Sensor              |
| Subseries          | 870                 |
| Gender             | Male                |
| Number of contacts | 3                   |
| Contact terminal   | Crimp               |
| Upper temperature  | +80 °C              |
| Lower temperature  | -25 °C              |
| Protection degree  | IP68                |
| Locking system     | Screw (7/8"-16 UN)  |
| Mating cycles      | >100                |
| Connector Diameter | 26 mm               |
| Cable Length       | 2 m                 |
| Cable diameter     | 7,4 mm              |
| Cable              | 3 x 1,5 PUR         |
| Wire-section       | 1.5 mm <sup>2</sup> |

### Electrical parameters

# Product data sheet

## Binder connectors

### Male angled connector



|                         |        |
|-------------------------|--------|
| Nominal current         | 13 A   |
| Nominal voltage         | 300 V  |
| Impuls voltage          | 2500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 3      |
| Overvoltage categorie   | II     |

## Material

|                     |              |
|---------------------|--------------|
| Jacket material     | PUR          |
| Material group      | II           |
| Material of insert  | PUR          |
| Material of housing | PUR          |
| Material of contact | CuZn (Brass) |
| Plating             | Au (Gold)    |
| Insulation wire     | TPM          |