

# Product data sheet

## Binder connectors


### Male panel mount connector



## Dip solder

86 0133 0000 00005

<https://www.ac-solutions.be/en/product/860133000000005>



## Specifications

### General Characteristics

|                    |               |
|--------------------|---------------|
| Screw size         | M12-B         |
| Series             | Sensor        |
| Subseries          | 715-766       |
| Gender             | Male          |
| Number of contacts | 5             |
| Contact terminal   | Dip solder    |
| Upper temperature  | +85 °C        |
| Lower temperature  | -40 °C        |
| Protection degree  | IP68          |
| Locking system     | Screw (M12-B) |
| Mating cycles      | >100          |
| Connector Diameter | 18 mm         |

### Electrical parameters

|                 |     |
|-----------------|-----|
| Nominal current | 4 A |
|-----------------|-----|

# Product data sheet

## Binder connectors

### Male panel mount connector



|                         |        |
|-------------------------|--------|
| Nominal voltage         | 125 V  |
| Impuls voltage          | 1500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 3      |
| Overvoltage categorie   | II     |

## Material

|                     |                                       |
|---------------------|---------------------------------------|
| Material group      | II                                    |
| Material of insert  | PA                                    |
| Material of housing | Brass / Zinc diecasting nickel plated |
| Material of contact | CuZn (Brass)                          |
| Plating             | Au (Gold)                             |