

# Product data sheet

## Binder connectors


### Male panel mount connector



Color code blue

99 9135 60 12

<https://www.ac-solutions.be/en/product/9991356012>



## Specifications

### General Characteristics

|                    |                      |
|--------------------|----------------------|
| Series             | Miniature            |
| Subseries          | 720                  |
| Gender             | Male                 |
| Number of contacts | 12                   |
| Contact terminal   | Solder               |
| Upper temperature  | +85 °C               |
| Lower temperature  | -25 °C               |
| Protection degree  | IP67                 |
| Locking system     | Snap-in              |
| Mating cycles      | >500                 |
| Connector Diameter | 16 mm                |
| Wire-section       | 0.25 mm <sup>2</sup> |

### Electrical parameters

|                 |      |
|-----------------|------|
| Nominal current | 2 A  |
| Nominal voltage | 60 V |

# Product data sheet

## Binder connectors

### Male panel mount connector



|                         |       |
|-------------------------|-------|
| Impuls voltage          | 800 V |
| Max. contact resistance | 3 m?  |
| Pollution degree        | 2     |
| Overvoltage categorie   | II    |

## Material

|                     |                |
|---------------------|----------------|
| Material group      | II             |
| Material of insert  | PA (UL 94 V-0) |
| Material of housing | PA (UL 94 V-0) |
| Material of contact | CuZn (Brass)   |
| Plating             | Au (Gold)      |