

# Product data sheet

## Binder connectors

### Female panel mount connector




## With dip solder termination

Lightgrey

99 9208 490 03

<https://www.ac-solutions.be/en/product/99920849003>



## Specifications

### General Characteristics

|                    |              |
|--------------------|--------------|
| Series             | Subminiature |
| Subseries          | 620          |
| Gender             | Female       |
| Number of contacts | 3            |
| Contact terminal   | Dip solder   |
| Upper temperature  | +85 °C       |
| Lower temperature  | -25 °C       |
| Protection degree  | IP67         |
| Locking system     | Snap-in      |
| Connector Diameter | 11.5 mm      |

### Electrical parameters

|                 |       |
|-----------------|-------|
| Nominal current | 3 A   |
| Nominal voltage | 125 V |

# Product data sheet

## Binder connectors

### Female panel mount connector



|                         |        |
|-------------------------|--------|
| Impuls voltage          | 1500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 2      |
| Overvoltage categorie   | II     |

## Material

|                     |                |
|---------------------|----------------|
| Material group      | II             |
| Material of insert  | PA (UL 94 V-0) |
| Material of housing | PA (UL 94 V-0) |
| Material of contact | CuSn (Bronze)  |
| Plating             | Au (Gold)      |