

# Product data sheet



## Ilme connectors

surface mounting housing, high, size 104.27, C-TYPE alu, 4 pegs, 2xPG21 side, cov.



CAP 24 CP2

<https://www.ac-solutions.be/en/product/cap24cp2>



## Specifications

### General characteristics

|                             |                                                                                                          |
|-----------------------------|----------------------------------------------------------------------------------------------------------|
| Enclosure type              | Surface mounting housing                                                                                 |
| Size                        | 104.27                                                                                                   |
| Enclosure series            | C-TYPE                                                                                                   |
| Closing type                | With 4 pegs                                                                                              |
| Locking mechanism           | Double locking levers                                                                                    |
| Protection degree           | IP65                                                                                                     |
| Ambient lower temperature   | -40 °C                                                                                                   |
| Ambient upper temperature   | 125 °C                                                                                                   |
| Operation lower temperature | -40 °C                                                                                                   |
| Operation upper temperature | 125 °C                                                                                                   |
| Cable entry type            | side cable entry                                                                                         |
| Cable entry size            | Pg21 x 2                                                                                                 |
| Position cable feed         | Two-sided                                                                                                |
| Height                      | 81 mm                                                                                                    |
| Width                       | 57 mm                                                                                                    |
| Length                      | 144 mm                                                                                                   |
| Remark                      | May be combined with enclosures: CHO 24 X,CAO 24 X,CHV 24 X,CAV 24 X,MHO 24 X,MAO 24 X,MHV 24 X,MAV 24 X |

# Product data sheet

## Ilme connectors

surface mounting housing, high, size 104.27, C-TYPE alu, 4 pegs, 2xPG21 side, cov.



### Material

|                                                            |                                                                           |
|------------------------------------------------------------|---------------------------------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                                                  |
| Coating housing                                            | With epoxy-polyester thermosetting powder coating                         |
| Inflammability class of insulation material acc. with UL94 | V2                                                                        |
| Extra information                                          | Corrosion resistant,UV resistant,With hinged lid,With interlocking device |