

female contact, 1,5mm², silver, crimp, 10A, series CD



CDFA 1.5

<https://www.ac-solutions.be/en/product/cdfa15>



TIN PLATED	SILVER PLATED	JE GOLD PLATED	PART PLATED	BARBERS GOLD PLATED	SPECIAL GOLD PLATED	HIGH NUMBER OF MATINGS SERIES	AW mm	WIRE GAUGE mm ² / AWG	IDENTIFICATION	B mm	STANDARD LENGTH mm
CDP5 0.3	CDPA 0.3	CDPJ0 0.3	CDPD0 0.3	CDPF0 0.3	CDP20 0.3	ROP20 0.3	0.80	0,14-0,37 28-22	1		
CDP5 0.5	CDPA 0.5	CDPJ0 0.5	CDPD0 0.5	CDPF0 0.5	CDP20 0.5	ROP20 0.5	1,90	0,25 20	2		
CDP5 0.7	CDPA 0.7	CDPJ0 0.7	CDPD0 0.7	CDPF0 0.7	CDP20 0.7	ROP20 0.7	1,30	0,75 18	3		
CDP5 1.0	CDPA 1.0	CDPJ0 1.0	CDPD0 1.0	CDPF0 1.0	CDP20 1.0	ROP20 1.0	1,45	1 16	3		
CDP5 1.5	CDPA 1.5	CDPJ0 1.5	CDPD0 1.5	CDPF0 1.5	CDP20 1.5	ROP20 1.5	1,55	1,5 14	4		
CDP5 2.5	CDPA 2.5	CDPJ0 2.5	CDPD0 2.5	CDPF0 2.5	CDP20 2.5	ROP20 2.5	2,2	2,5 14	5		

23/02/18 Added new part numbers - HIGH NUMBER OF MATINGS (HNM)

23/02/17 Changed part numbers - CDP-20 was CDP XX-3 and CDP-25 was CDPD XX-2

02/05/10 Added new part numbers - TIN PLATED

06/02/12 Added new part numbers - JE and SPECIAL GOLD PLATED

Dimensions in mm

Date: 16/03/07

Sign: T. Tedeschi

CFD XX

Female crimp contact 10A

Scale

2:1

Specifications

General characteristics

Connection type	Turned crimp
Contact type (gender)	Female
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Min. Cross section	1.5 mm²
Max. Cross section	1.5 mm²
AWG size	16
Identification	4
Diameter male contact	1.6 mm
Wire strip length	8 mm

Electrical parameters

Max. rated current	10 A
--------------------	------

Material

Material contact	Copper alloy
Plating of contact	Silver