

female contact, 0,75mm², gold, crimp, 10A, series CD



CDFD 0.7

<https://www.ac-solutions.be/en/product/cdfd07>



Draufschauen! Always reversed

TIN PLATED	SILVER PLATED	GOLD PLATED	GOLD PLATED	SPECIAL GOLD PLATED	HIGH NUMBER OF MATINGS (HNM)	AWG	WIRE GAUGE	IDENTIFICATION	Ø mm	STRIKING LENGTH mm
ODFA 0.3	ODFA 0.3	ODFD 0.3	ODFD 0.3	ODFD 0.3	ODFD 0.3	0.80	0.14-0.37	26-22	1	
ODFS 0.8	ODFA 0.8	ODFD 0.8	ODFD 0.8	ODFD 0.8	ODFD 0.8	1.00	0.35	20	2	
ODFS 0.7	ODFA 0.7	ODFD 0.7	ODFD 0.7	ODFD 0.7	ODFD 0.7	1.30	0.75	16	2	
ODFS 1.0	ODFA 1.0	ODFD 1.0	ODFD 1.0	ODFD 1.0	ODFD 1.0	1.45	1	16	3	
ODFS 1.5	ODFA 1.5	ODFD 1.5	ODFD 1.5	ODFD 1.5	ODFD 1.5	1.6	1.5	16	4	
ODFS 2.0	ODFA 2.0	ODFD 2.0	ODFD 2.0	ODFD 2.0	ODFD 2.0	2.2	2.0	14	5	

23/02/18	Added new part numbers - HIGH NUMBER OF MATINGS (HNM)
23/02/17	Changed part numbers - CDFD was CDFD XX.1 and CDFD was CDFD XX.2
02/05/16	Added new part numbers - TIN PLATED
06/02/12	Added new part numbers - JET and SPECIAL GOLD PLATED

dimensions in mm
Date: 16/03/07
Sign: T. Tedeschi

CDF XX
Female crimp contact 10A

Scale
2:1

Specifications

General characteristics

Connection type	Turned crimp
Contact type (gender)	Female
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Min. Cross section	0.75 mm²
Max. Cross section	0.75 mm²
AWG size	18
Identification	?
Diameter male contact	1.6 mm
Wire strip length	8 mm

Electrical parameters

Max. rated current	10 A
--------------------	------

Material

Material contact	Copper alloy
Plating of contact	Gold