

Product data sheet


Ilme connectors

surface mounting housing, size 104.27, C-TYPE alu, 4 pegs, 2xPG21 side, cov.



CHP 24 CP2

<https://www.ac-solutions.be/en/product/chp24cp2>



Specifications

General characteristics

Enclosure type	Surface mounting housing
Size	104.27
Enclosure series	C-TYPE
Closing type	With 4 pegs
Locking mechanism	Double locking levers
Protection degree	IP65
Ambient lower temperature	-40 °C
Ambient upper temperature	125 °C
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Cable entry type	side cable entry
Cable entry size	Pg21 x 2
Position cable feed	Two-sided
Height	63 mm
Width	57 mm
Length	144 mm
Remark	May be combined with enclosures: CHO 24 X, CAO 24 X, CHV 24 X, CAV 24 X, MHO 24 X, MAO 24 X, MHV 24 X, MAV 24 X

Product data sheet

Ilme connectors

surface mounting housing, size 104.27, C-TYPE alu, 4 pegs, 2xPG21 side, cov.



Material

Material housing	Die cast aluminium alloy
Coating housing	With epoxy-polyester thermosetting powder coating
Inflammability class of insulation material acc. with UL94	V2
Extra information	Corrosion resistant,UV resistant,With hinged lid,With interlocking device