

Product data sheet



Ilme connectors - CTSE 10 P + PE

female insert, size 57.27, 10p+PE, silver, spring, 16A, 500V, right



CTSEF 10 R

<https://www.ac-solutions.be/en/product/ctsef10r>



Specifications

General characteristics

Product Type	Standard insert
Insert series	CTSE
Number of contacts	10 + PE
Number of poles	10
Connection type	Spring terminal connection
Gender	Female
Size	57.27
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
AWG-range 1	26
AWG-range 2	14
Min. Cross section without end sleeve	0.75 mm ²
Max. Cross section without end sleeve	2.5 mm ²
Min. Cross section	0.14 mm ²
Max. Cross section	2.5 mm ²
Colour	Grey
Extra information	Modular version,With protective conductor,With wire protection

Product data sheet

Ilme connectors - CTSE 10 P + PE

female insert, size 57.27, 10p+PE, silver, spring, 16A, 500V, right



Remark	Only for bulkhead mounted housing and BIG HOODS
--------	---

Electrical parameters

Max. rated current	16 A
Nominal rated voltage	500 V
Over voltage category	III
Rated surge voltage	6 kV
Pollution degree	3

Material

Material insert	Thermoplastic
Material contact	Copper alloy
Plating of contact	Silver
Inflammability class of insulation material acc. with UL94	V0