

# Product data sheet

## Ilme connectors

hood, high, size 57.27, 180°C alu, 4 pegs, 1xM32 top




MAVR 10.32


<https://www.ac-solutions.be/en/product/mavr1032>




CHOR (CAOR) - MHOR (MAOR)



CHVR (CAVR) - MHVR (MAVR)



CHCR G



## Specifications

### General characteristics

|                             |                       |
|-----------------------------|-----------------------|
| Enclosure type              | Hood                  |
| Size                        | 57.27                 |
| Enclosure series            | 180°C                 |
| Closing type                | With 4 pegs           |
| Locking mechanism           | Double locking levers |
| Protection degree           | IP65 / IP66 / IP69    |
| Ambient lower temperature   | -40 °C                |
| Ambient upper temperature   | 180 °C                |
| Operation lower temperature | -40 °C                |
| Operation upper temperature | 180 °C                |
| Cable entry type            | top cable entry       |
| Cable entry size            | M32                   |
| Position cable feed         | Top entry             |
| Height                      | 85 mm                 |
| Width                       | 43 mm                 |
| Length                      | 73 mm                 |

## Material

# Product data sheet

## Ilme connectors

hood, high, size 57.27, 180°C alu, 4 pegs, 1xM32 top



|                                                            |                                                                                     |
|------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                                                            |
| Coating housing                                            | With special thermosetting powder coating with high resistance to high temperatures |
| Inflammability class of insulation material acc. with UL94 | V2                                                                                  |
| Extra information                                          | Corrosion resistant,UV resistant,With interlocking device                           |