

Product data sheet

Ilme connectors

hood, high, size 77.27, C-TYPE alu, 4 pegs, 2xM25 top, no adaptor




MFV 16.225


<https://www.ac-solutions.be/en/product/mfv16225>



CZAV L2 - (MZAV L2) - [MZFV L2]



CAV - MAV - MFV



Specifications

General characteristics

Enclosure type	Hood
Size	77.27
Enclosure series	C-TYPE
Closing type	With 4 pegs
Locking mechanism	Double locking levers
Protection degree	IP65 / IP66 / IP69
Ambient lower temperature	-40 °C
Ambient upper temperature	125 °C
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Cable entry type	double top cable entry
Cable entry size	M25 x 2
Position cable feed	Top entry
Height	76 mm
Width	43 mm
Length	93.5 mm
Remark	Enclosures without adaptor, threaded on the body, to be used only with a complete cable gland

Product data sheet

Ilme connectors

hood, high, size 77.27, C-TYPE alu, 4 pegs, 2xM25 top, no adaptor



Material

Material housing	Die cast aluminium alloy
Coating housing	With epoxy-polyester thermosetting powder coating
Inflammability class of insulation material acc. with UL94	V2
Extra information	Corrosion resistant,UV resistant,With interlocking device