

# Product data sheet


## Ilme connectors

surface mounting housing, size 77.27, C-TYPE alu, 4 pegs, 1xM25 side, cover plastic




MHP 16 CP25


<https://www.ac-solutions.be/en/product/mhp16cp25>



CHP CAP - MHP MAP



CHP CS/CP CAP CS/CP - MHP CS/CP MAP CS/CP



|                 | A  |
|-----------------|----|
| CHP / MHP       | 63 |
| CAP / MAP       | 77 |
| CHP CS / MHP CS | 63 |
| CAP CS / MAP CS | 77 |
| CHP CP / MHP CP | 63 |
| CAP CP / MAP CP | 77 |

## Specifications

### General characteristics

|                             |                                                                                                                 |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------|
| Enclosure type              | Surface mounting housing                                                                                        |
| Size                        | 77.27                                                                                                           |
| Enclosure series            | C-TYPE                                                                                                          |
| Closing type                | With 4 pegs                                                                                                     |
| Locking mechanism           | Double locking levers                                                                                           |
| Protection degree           | IP65                                                                                                            |
| Ambient lower temperature   | -40 °C                                                                                                          |
| Ambient upper temperature   | 125 °C                                                                                                          |
| Operation lower temperature | -40 °C                                                                                                          |
| Operation upper temperature | 125 °C                                                                                                          |
| Cable entry type            | side cable entry                                                                                                |
| Cable entry size            | M25                                                                                                             |
| Position cable feed         | Side entry                                                                                                      |
| Height                      | 63 mm                                                                                                           |
| Width                       | 57 mm                                                                                                           |
| Length                      | 117 mm                                                                                                          |
| Remark                      | May be combined with enclosures: CHO 16 X, CAO 16 X, CHV 16 X, CAV 16 X, MHO 16 X, MAO 16 X, MHV 16 X, MAV 16 X |

# Product data sheet

## Ilme connectors

surface mounting housing, size 77.27, C-TYPE alu, 4 pegs, 1xM25 side, cover plastic



### Material

|                                                            |                                                                           |
|------------------------------------------------------------|---------------------------------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                                                  |
| Coating housing                                            | With epoxy-polyester thermosetting powder coating                         |
| Inflammability class of insulation material acc. with UL94 | V2                                                                        |
| Extra information                                          | Corrosion resistant,UV resistant,With hinged lid,With interlocking device |