

Product data sheet


Ilme connectors

surface mounting housing, size 66.40, C-TYPE alu, 4 pegs, 2xM40 side, cover metal




MHP 50 CS240


<https://www.ac-solutions.be/en/product/mhp50cs240>



CHP - MHP



CHP CS - MHP CS



Specifications

General characteristics

Enclosure type	Surface mounting housing
Size	66.40
Enclosure series	C-TYPE
Closing type	With 4 pegs
Locking mechanism	Double locking levers
Protection degree	IP65
Ambient lower temperature	-40 °C
Ambient upper temperature	125 °C
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Cable entry type	side cable entry
Cable entry size	M40 x 2
Position cable feed	Two-sided
Height	82 mm
Width	57.3 mm
Length	106 mm
Remark	May be combined with enclosures: CHO 50 X,cao 50 X,CAV 50 X,MHO 50 X,MAO 50 X,MFO 50 X,MAV 50 X,MFV 50 X

Product data sheet

Ilme connectors

surface mounting housing, size 66.40, C-TYPE alu, 4 pegs, 2xM40 side, cover metal



Material

Material housing	Die cast aluminium alloy
Coating housing	With epoxy-polyester thermosetting powder coating
Inflammability class of insulation material acc. with UL94	V2
Extra information	Corrosion resistant,UV resistant,With hinged lid,With interlocking device