

# Product data sheet

## Ilme connectors

hood, high, size 66.16, IL-BRID alu, 2 pegs, 1xM25 top



MZAV 25 L25

<https://www.ac-solutions.be/en/product/mzav25l25>



## Specifications

### General characteristics

|                             |                              |
|-----------------------------|------------------------------|
| Enclosure type              | Hood                         |
| Size                        | 66.16                        |
| Enclosure series            | IL-BRID                      |
| Closing type                | With 2 pegs                  |
| Locking mechanism           | Single locking lever         |
| Protection degree           | IP66 / IP67 / IP69           |
| Ambient lower temperature   | -40 °C                       |
| Ambient upper temperature   | 125 °C                       |
| Operation lower temperature | -40 °C                       |
| Operation upper temperature | 125 °C                       |
| Cable entry type            | top cable entry with adapter |
| Cable entry size            | M25                          |
| Position cable feed         | Top entry                    |
| Height                      | 85.5 mm                      |
| Width                       | 36 mm                        |
| Length                      | 79.5 mm                      |

### Material

# Product data sheet

## Ilme connectors

hood, high, size 66.16, IL-BRID alu, 2 pegs, 1xM25 top



|                                                            |                                                           |
|------------------------------------------------------------|-----------------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                                  |
| Coating housing                                            | With epoxy-polyester powder coating                       |
| Inflammability class of insulation material acc. with UL94 | V2                                                        |
| Extra information                                          | Corrosion resistant,UV resistant,With interlocking device |