

# Product data sheet



## Ilme connectors - RDSH 9 P + PE

male insert, size 44.27, 9p+PE, SQUICH, 10A, 400V, HNM



RDSHM 09

<https://www.ac-solutions.be/en/product/rdshm09>



## Specifications

### General characteristics

|                             |                                                  |
|-----------------------------|--------------------------------------------------|
| Product Type                | Standard insert                                  |
| Insert series               | RDSH (HNM)                                       |
| Number of contacts          | 9 + PE                                           |
| Number of poles             | 9 + PE                                           |
| Connection type             | SQUICH® spring terminal connection without tools |
| Gender                      | Male                                             |
| Size                        | 44.27                                            |
| Operation lower temperature | -40 °C                                           |
| Operation upper temperature | 125 °C                                           |
| AWG-range 1                 | 26                                               |
| AWG-range 2                 | 14                                               |
| Min. Cross section          | 0.14 mm <sup>2</sup>                             |
| Max. Cross section          | 2.5 mm <sup>2</sup>                              |
| Colour                      | Grey                                             |

### Electrical parameters

|                       |       |
|-----------------------|-------|
| Max. rated current    | 10 A  |
| Nominal rated voltage | 400 V |

# Product data sheet

## Ilme connectors - RDSH 9 P + PE

male insert, size 44.27, 9p+PE, SQUICH, 10A, 400V, HNM



|                     |      |
|---------------------|------|
| Rated surge voltage | 6 kV |
| Pollution degree    | 3    |

### Material

|                                                            |               |
|------------------------------------------------------------|---------------|
| Material insert                                            | Thermoplastic |
| Material contact                                           | Copper alloy  |
| Plating of contact                                         | Gold          |
| Inflammability class of insulation material acc. with UL94 | V0            |