

# Product data sheet


## Ilme connectors

surface mounting housing, high, size 77.27, T-TYPE W plastic, 2 levers, 1xM40 side



TAPW 16.40

<https://www.ac-solutions.be/en/product/tapw1640>



## Specifications

### General characteristics

|                             |                          |
|-----------------------------|--------------------------|
| Enclosure type              | Surface mounting housing |
| Size                        | 77.27                    |
| Enclosure series            | T-TYPE /W                |
| Closing type                | With 2 levers            |
| Locking mechanism           | Double locking levers    |
| Protection degree           | IP66 / IP69              |
| Ambient lower temperature   | -40 °C                   |
| Ambient upper temperature   | 90 °C                    |
| Operation lower temperature | -40 °C                   |
| Operation upper temperature | 90 °C                    |
| Cable entry type            | side cable entry         |
| Cable entry size            | M40                      |
| Position cable feed         | Two-sided                |
| Height                      | 80 mm                    |
| Width                       | 57 mm                    |
| Length                      | 117 mm                   |

## Material

# Product data sheet

## Ilme connectors

surface mounting housing, high, size 77.27, T-TYPE W plastic, 2 levers, 1xM40 side



|                                                            |                                                           |
|------------------------------------------------------------|-----------------------------------------------------------|
| Material housing                                           | Thermoplastic                                             |
| Coating housing                                            | Uncoated                                                  |
| Inflammability class of insulation material acc. with UL94 | V0                                                        |
| Extra information                                          | Corrosion resistant,UV resistant,With interlocking device |