

# Product data sheet

Techno connectors


Plug connector D7-13.5



## IP68/IP69

THB.408.A2B

<https://www.ac-solutions.be/en/product/thb408a2b>



## Specifications

### General Characteristics

|                           |                                                                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Series                    | TEEPLUG                                                                                                                                                                          |
| Subseries                 | TH408                                                                                                                                                                            |
| Number of contacts        | 3                                                                                                                                                                                |
| Gender                    | Male                                                                                                                                                                             |
| Contact terminals         | Contact screw terminals. For cable section 1.0 mm <sup>2</sup>                                                                                                                   |
| Cable section             | max 4,0                                                                                                                                                                          |
| Min-max cable diameter    | 7,0 - 13,5 mm                                                                                                                                                                    |
| Protection degree         | IP68/IP69                                                                                                                                                                        |
| Protection degree details | IP 68 0,5 bar (5 m / 1 h)                                                                                                                                                        |
| Lower temperature         | -40 °C                                                                                                                                                                           |
| Upper temperature         | +125 °C                                                                                                                                                                          |
| Pollution degree          | 2                                                                                                                                                                                |
| Note                      | Every connector housing type can be equipped with male or female contacts. For reasons pertaining to safety, only female contacts may be used in the live part of the connector. |
| Max. temperature          | T125                                                                                                                                                                             |

# Product data sheet

## Techno connectors

### Plug connector D7-13.5



|                |              |
|----------------|--------------|
| Standards      | EN61984:2001 |
| Tracking index | PTI 175      |

## Electrical parameters

|                           |       |
|---------------------------|-------|
| Rated current             | 25 A  |
| Rated voltage             | 400 V |
| Impulse withstand voltage | 4 kV  |

## Material

|                            |                                                             |
|----------------------------|-------------------------------------------------------------|
| Impulse withstand category | II                                                          |
| Lock nuts                  | PA66 GF UL94 V0 GWT 960°C black - grey RAL 7035             |
| Connector housing          | PA66 UL94 V0/V2 GWT 850°C black - grey RAL 7035             |
| Terminal block housing     | PA66 GF UL94 V0 GWT 960°C black - grey RAL 7035             |
| Grommets                   | TPE/silicon                                                 |
| Seals                      | TPE/silicon                                                 |
| Contact screw terminals    | Brass nickel plated OR Brass silver plated (THX.408.XXX.AG) |
| Standard/Piercing screws   | M3 steel zinc plated                                        |