

# Product data sheet


## Ilme connectors

hood, high, size 104.27, T-TYPE plastic, 4 pegs, 1xM40 side



TMAO 24.40

<https://www.ac-solutions.be/en/product/tmao2440>



## Specifications

### General characteristics

|                             |                       |
|-----------------------------|-----------------------|
| Enclosure type              | Hood                  |
| Size                        | 104.27                |
| Enclosure series            | T-TYPE                |
| Closing type                | With 4 pegs           |
| Locking mechanism           | Double locking levers |
| Protection degree           | IP65                  |
| Ambient lower temperature   | -40 °C                |
| Ambient upper temperature   | 90 °C                 |
| Operation lower temperature | -40 °C                |
| Operation upper temperature | 90 °C                 |
| Cable entry type            | side cable entry      |
| Cable entry size            | M40                   |
| Position cable feed         | Side entry            |
| Height                      | 80 mm                 |
| Width                       | 46 mm                 |
| Length                      | 123 mm                |

## Material

# Product data sheet

## Ilme connectors

hood, high, size 104.27, T-TYPE plastic, 4 pegs, 1xM40 side



|                                                            |                                                           |
|------------------------------------------------------------|-----------------------------------------------------------|
| Material housing                                           | Thermoplastic                                             |
| Coating housing                                            | Uncoated                                                  |
| Inflammability class of insulation material acc. with UL94 | V0                                                        |
| Extra information                                          | Corrosion resistant,UV resistant,With interlocking device |