

# Product data sheet

## Yamaïchi connectors

Straight cable plug with back nut for Bend Relief



### + Bend Relief (051,Black)


YCP-TPR09ACX-04MSEEX-051B

YCP-TPR09ACX-04MSEEX-051B


<https://www.ac-solutions.be/en/product/ycptpr09acx04mseex051b>



Dimensions [mm]  
D1= 9.3 L1= ~42.1 W1= 8.0  
L2= ~32.0 W2= 8.0  
L3= 4.6



Dimensions [mm]  
D1= 5.1  
D2= >4.5  
D3= 5.3



## Specifications

### General Characteristics

|                            |                      |
|----------------------------|----------------------|
| Pin count                  | 4 Pins               |
| Size                       | Size 09              |
| Housing variant            | Standard             |
| Insulator Variant          | Standard             |
| IP Grade (to contact)      | IP68                 |
| IP Grade (to housing)      | IP50                 |
| Mating cycles              | 5000 Times           |
| Min. operating temperature | -20 °C               |
| Max. operating temperature | +120 °C              |
| Short Term Max. Temp       | +200 °C              |
| Vibration [Hz]             | 20 [10 Hz - 2000 Hz] |
| Shock resistance           | 50 [ 6 ms]           |
| Salt Spray Corrosion       | >144 Hours           |
| Shielding (10 MHz)         | >75 Db               |

# Product data sheet

## Yamaichi connectors

### Straight cable plug with back nut for Bend Relief



|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Shielding (1 GHz)                 | >55 Db                            |
| Contact Diameter                  | 0.7 mm                            |
| Terminal cross section            | Max AWG 22 / 0,34 mm <sup>2</sup> |
| Contact Type                      | Male: Solder Contacts             |
| Cable collet type                 | 51                                |
| Cable diameter range              | >4,5 to 5,1 mm                    |
| RoHS                              | 2011/65/EU (2015/863/EU)          |
| Bend relief part number           | YCP-ABR09BT051X                   |
| Bend relief cable diameter range  | >4,5 to 5,1 mm                    |
| Bend relief colour                | Black                             |
| Bend relief operating temperature | -40 to 110 °C                     |
| Bend relief L1                    | 5.5 mm                            |
| Bend relief L2                    | 21.5 mm                           |

## Electrical Parameters

|                                  |        |
|----------------------------------|--------|
| Current rating per contact       | 7 A    |
| Test Voltage Contact-Contact RMS | 0.8 kV |
| Test Voltage Contact-Shell RMS   | 0.8 kV |
| Contact Resistance               | 6,5 ?  |

## Material

|                              |                                  |
|------------------------------|----------------------------------|
| Connector type digit         | PR                               |
| Housing Material             | Brass                            |
| Housing surface              | Chrome                           |
| Contact Material and Surface | CuZn38Pb2 / min 0.75µm Au        |
| Material Cable Sealing       | FKM, black                       |
| Insulator Material           | PEEK (UL)                        |
| Bend relief material         | TPU (Thermoplastic polyurethane) |