Product sheet

Subminiature connector





Product Pole

Contacts: 3, Male panel mount connector, solder, screwed from front

Area Article number M9 IP67 Series 712/702 09 0407 80 03

Illustration





You can find the assembly instruction on the next page.

Technical data

Common values

Connector Design Connector locking system Termination Wire gauge (mm) Wire gauge (AWG) Cable outlet Upper temperature

Lower temperature

Cable data

material housing Insulation single lead Single lead structure Conductor resistance Male panel mount connector screw

Solder 0.25 mm² 24

85 °C -40 °C

Electrical values

Rated voltage 125 V Rated impulse voltage 1500 V Pollution degree Overvoltage category Ш Material group Ш Rated current (40°C) 4 A Volume resistivity $\leq 3 \text{ m}\Omega$ EMV compliance shieldable Degree of protection IP67 Mechanical operation > 500 mating cycles

Material

Material of contact Contact plating Material of contact body Material of housing

CuZn (Brass) Au (Gold) PA (UL 94 V-0) CuZn (Brass nickel-plated)

Contacts: 3, Male panel mount connector, solder, screwed from front

Product sheet

Subminiature connector



Product

Contacts: 3, Male panel mount connector, solder, screwed from front

Area Article number M9 IP67 Series 712/702 09 0407 80 03

Pole

3

