Product sheet

Miniature connector



Product Contacts


Contacts: 7, female panel mount connector, screwed from front, IP 67,


shielded

Pole 7

Area Article number Push-Pull IP67 Series 440 09 4828 81 07

Illustration





Contact Arrangement

You can find the item description and assembly instruction on the next page.

Technical data

Common values

Connector Design Connector locking system Termination Wire gauge (mm) Wire gauge (AWG) Cable outlet Upper temperature Lower temperature Female panel mount connector Push-Pull Solder 0.75 mm² 20 -85 °C -40 °C

Electrical values

Rated voltage 125 V Rated impulse voltage 800 V Pollution degree Overvoltage category Material group Ш Rated current (40°C) 5 A Volume resistivity $\leq 3 \text{ m}\Omega$ EMV compliance shielded Degree of protection > 1000 mating cycles Mechanical operation

Material

 Material of contact
 CuSn (Bronze)

 Contact plating
 Au (Gold)

 Material of contact body
 PBT (UL 94 V-0)

 Material of housing
 CuZn (Brass nickel-plated)

Contacts: 7, female panel mount connector, screwed from front, IP 67, shielded

Product sheet

Miniature connector



Product

Pole

Contacts: 7, female panel mount connector, screwed from front, IP 67,

nielded

snieid

Area Article number Push-Pull IP67 Series 440 09 4828 81 07

