

# Product data sheet


## Binder connectoren

### Male cable connector



09 0059 00 05

<https://www.ac-solutions.be/nl/product/0900590005>



## Specificaties

### General Characteristics

|                    |                     |
|--------------------|---------------------|
| Series             | Power               |
| Subseries          | 690                 |
| Gender             | Male                |
| Number of contacts | 5                   |
| Contact terminal   | Solder              |
| Upper temperature  | +85 °C              |
| Lower temperature  | -40 °C              |
| Protection degree  | IP40                |
| Locking system     | Bayonet             |
| Mating cycles      | >500                |
| Connector Diameter | 29 mm               |
| Cable outlet       | 5-8 mm              |
| Wire-section       | 2.5 mm <sup>2</sup> |

### Electrical parameters

|                 |        |
|-----------------|--------|
| Nominal current | 10 A   |
| Nominal voltage | 250 V  |
| Impuls voltage  | 2500 V |

# Product data sheet

## Binder connectoren

### Male cable connector



|                         |      |
|-------------------------|------|
| Max. contact resistance | 5 m? |
| Pollution degree        | 1    |
| Overvoltage categorie   | II   |

## Material

|                     |                  |
|---------------------|------------------|
| Material group      | III              |
| Material of insert  | PET (UL 94 V-0)  |
| Material of housing | GD-Al (anodized) |
| Material of contact | CuZn (Brass)     |
| Plating             | Ag (Silver)      |