

# Product data sheet

## Binder connectoren


### Female panel mount connector



## With flexible PCB, front fastened

09 0174 65 08

<https://www.ac-solutions.be/nl/product/0901746508>



## Specificaties

### General Characteristics

|                    |                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------|
| Screw size         | M16                                                                                       |
| Series             | Miniature                                                                                 |
| Subseries          | 423-723-425                                                                               |
| Gender             | Female                                                                                    |
| Number of contacts | 8                                                                                         |
| Contact terminal   | Dip solder                                                                                |
| Upper temperature  | +95 °C                                                                                    |
| Lower temperature  | -40 °C                                                                                    |
| Protection degree  | IP67                                                                                      |
| Locking system     | Screw (M16)                                                                               |
| Mating cycles      | >500                                                                                      |
| Connector Diameter | 20 mm                                                                                     |
| Remark*            | *In case of pollution degree 2, overvoltage category II rated voltage is reduced to 32 V. |

### Electrical parameters

|                         |           |
|-------------------------|-----------|
| Nominal current         | 5 A       |
| Nominal voltage         | 60 (32) V |
| Impuls voltage          | 500 V     |
| Max. contact resistance | 5 m?      |

# Product data sheet

## Binder connectoren

### Female panel mount connector



|                       |         |
|-----------------------|---------|
| Pollution degree      | 1 (2)*  |
| Overvoltage categorie | I (II)* |

## Material

|                     |                               |
|---------------------|-------------------------------|
| Material group      | III                           |
| Material of insert  | PBT (UL 94 V-0)               |
| Material of housing | Zinc diecasting nickel plated |
| Material of contact | CuSn (Bronze)                 |
| Plating             | Ag (Silver)                   |