

# Product data sheet

## Binder connectoren


### Female panel mount connector



## Dip solder, front fastened with shielding sheet, angled

09 0404 55 02

<https://www.ac-solutions.be/nl/product/0904045502>



## Specificaties

### General Characteristics

|                    |              |
|--------------------|--------------|
| Screw size         | M9           |
| Series             | Subminiature |
| Subseries          | 712-702      |
| Gender             | Female       |
| Number of contacts | 2            |
| Contact terminal   | Dip solder   |
| Upper temperature  | +85 °C       |
| Lower temperature  | -40 °C       |
| Protection degree  | IP67         |
| Locking system     | Screw (M9)   |
| Mating cycles      | >500         |

### Electrical parameters

|                 |       |
|-----------------|-------|
| Nominal current | 4 A   |
| Nominal voltage | 125 V |

# Product data sheet

## Binder connectoren

### Female panel mount connector



|                         |        |
|-------------------------|--------|
| Impuls voltage          | 1500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 1      |
| Overvoltage categorie   | II     |

## Material

|                     |                            |
|---------------------|----------------------------|
| Material group      | III                        |
| Material of insert  | PA (UL 94 V-0)             |
| Material of housing | CuZn (Brass nickel plated) |
| Material of contact | CuSn (Bronze)              |
| Plating             | Au (Gold)                  |