

# Product data sheet

## Binder connectoren


### Adapter



## Male connector M8 - female connector M12

09 5283 00 03

<https://www.ac-solutions.be/nl/product/0952830003>



## Specificaties

### General Characteristics

|                    |               |
|--------------------|---------------|
| Screw size         | M12/M8        |
| Series             | Sensor        |
| Subseries          | 765           |
| Gender             | Male & Female |
| Number of contacts | 3             |
| Upper temperature  | +85 °C        |
| Lower temperature  | -25 °C        |
| Protection degree  | IP67          |
| Locking system     | Screw         |
| Mating cycles      | >100          |
| Connector Diameter | 12 - 14,5 mm  |

### Electrical parameters

|                 |      |
|-----------------|------|
| Nominal current | 4 A  |
| Nominal voltage | 60 V |

# Product data sheet

## Binder connectoren

### Adapter



|                         |        |
|-------------------------|--------|
| Impuls voltage          | 1500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 3      |
| Overvoltage categorie   | II     |

## Material

|                     |                                   |
|---------------------|-----------------------------------|
| Material group      | II                                |
| Material of insert  | PUR                               |
| Material of housing | Hot melt                          |
| Material of contact | Pin CuZn (Brass), Socket (Bronze) |
| Plating             | Au (Gold)                         |