

# Product data sheet

Hummel connectoren

Inserts 12-pole





## Pinout counter-clockwise, Signal

Pins

7.002.912.127

<https://www.ac-solutions.be/nl/product/7002912127>



## Specificaties

### General Characteristics

|                      |                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------|
| Size                 | M23 Signal                                                                                              |
| Number of contacts   | 12                                                                                                      |
| Gender               | Male                                                                                                    |
| Pinout               | Counter-clockwise                                                                                       |
| Upper temperature    | +125 °C                                                                                                 |
| Lower temperature    | -40 °C                                                                                                  |
| Locking              | Screw locking   Twilock                                                                                 |
| Protection degree    | IP67/IP69K                                                                                              |
| Terminal type        | Dip-solder                                                                                              |
| Included contacts    | dip solder length 10 mm                                                                                 |
| Contact diameter     | 1 mm                                                                                                    |
| Coding possibilities | N, S, H, X, Y & Z                                                                                       |
| Remark               | The correct dimension of a connector with dip solder contacts depends on the particular type of housing |

# Product data sheet

## Hummel connectoren

### Inserts 12-pole



## Electrical Parameters

|                                         |                      |
|-----------------------------------------|----------------------|
| Nominal voltage (degree of pollution 3) | 200 V~               |
| Test voltage                            | 2500 V~              |
| Nominal current                         | 8 A                  |
| Insulation resistance                   | > 10 <sup>12</sup> ? |
| Max. contact resistance                 | 3 m?                 |

## Material

|          |                                                       |
|----------|-------------------------------------------------------|
| Material | Thermoplastic Polyamid PA 6/Fire protection class V-0 |
|----------|-------------------------------------------------------|