

# Product data sheet

## Binder connectoren


### Male angled connector



## Moulded

77 3427 0000 50003 0200

<https://www.ac-solutions.be/nl/product/7734270000500030200>



## Specificaties

### General Characteristics

|                    |                |
|--------------------|----------------|
| Screw size         | M12-A          |
| Series             | Sensor         |
| Subseries          | 763            |
| Gender             | Male           |
| Number of contacts | 3              |
| Contact terminal   | Crimp, moulded |
| Upper temperature  | +85 °C         |
| Lower temperature  | -25 °C         |
| Protection degree  | IP68           |
| Locking system     | Screw (M12-A)  |
| Mating cycles      | >100           |
| Connector Diameter | 14.5 mm        |
| Cable Length       | 2 m            |
| Cable diameter     | 4,5 mm         |
| Wire-section       | 0.34 mm²       |

# Product data sheet

## Binder connectoren

### Male angled connector



## Electrical parameters

|                         |        |
|-------------------------|--------|
| Nominal current         | 4 A    |
| Nominal voltage         | 250 V  |
| Impuls voltage          | 2500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 3      |
| Overvoltage categorie   | II     |

## Material

|                     |              |
|---------------------|--------------|
| Jacket material     | PUR          |
| Material group      | II           |
| Material of insert  | PUR          |
| Material of housing | PUR          |
| Material of contact | CuZn (Brass) |
| Plating             | Au (Gold)    |
| Insulation wire     | PVC          |