

Product data sheet

Binder connectoren


Female terminating connector



CAN-bus

77 9840 0000 00005

<https://www.ac-solutions.be/nl/product/779840000000005>



Pinbeleging Pin assignment

- 1 nicht konfektioniert / not assembled
- 2 nicht konfektioniert / not assembled
- 3 nicht konfektioniert / not assembled
- 4  Widerstand / Resistor
- 5  120 Ω

Specificaties

General Characteristics

Screw size	M12-A
Series	Sensor
Subseries	763
Gender	Female
Number of contacts	5
Contact terminal	Crimp, moulded
Upper temperature	+85 °C
Lower temperature	-25 °C
Protection degree	IP67
Locking system	Screw (M12-A)
Mating cycles	>100
Connector Diameter	14.5 mm
Cable diameter	7,2 mm
Wire-section	0,1 to 0,75 mm ²

Electrical parameters

Product data sheet

Binder connectoren

Female terminating connector



Nominal current	4 A
Nominal voltage	60 V
Impuls voltage	1500 V
Max. contact resistance	3 m?
Pollution degree	3
Overvoltage categorie	II

Material

Material group	II
Material of insert	PUR
Material of housing	PUR
Material of contact	CuSn (Bronze)
Plating	Au (Gold)