

# Product data sheet

## Binder connectoren


### Female cable connector



## Moulded, snap-in version, 8mm

79 3410 15 03

<https://www.ac-solutions.be/nl/product/7934101503>



## Specificaties

### General Characteristics

|                    |                      |
|--------------------|----------------------|
| Series             | Sensor               |
| Subseries          | 718                  |
| Gender             | Female               |
| Number of contacts | 3                    |
| Contact terminal   | Crimp, moulded       |
| Upper temperature  | +70 °C               |
| Lower temperature  | -25 °C               |
| Protection degree  | IP65                 |
| Locking system     | Snap-in              |
| Mating cycles      | >50                  |
| Connector Diameter | 9 mm                 |
| Cable Length       | 5 m                  |
| Cable diameter     | 3 mm                 |
| Wire-section       | 0.14 mm <sup>2</sup> |

## Electrical parameters

# Product data sheet

## Binder connectoren

### Female cable connector



|                         |       |
|-------------------------|-------|
| Nominal current         | 3 A   |
| Nominal voltage         | 60 V  |
| Impuls voltage          | 800 V |
| Max. contact resistance | 3 m?  |
| Pollution degree        | 3     |
| Overvoltage categorie   | II    |

## Material

|                     |              |
|---------------------|--------------|
| Jacket material     | PUR          |
| Material group      | II           |
| Material of insert  | PUR          |
| Material of housing | PUR          |
| Material of contact | CuZn (Brass) |
| Plating             | Au (Gold)    |
| Insulation wire     | PVC          |