

# Product data sheet

## Binder connectoren


### Male cable connector



## Metal locking system, screw clamp connection, solder termination on 12 pol

99 0429 314 04

<https://www.ac-solutions.be/nl/product/99042931404>



## Specificaties

### General Characteristics

|                    |                      |
|--------------------|----------------------|
| Screw size         | M12-A                |
| Series             | Sensor               |
| Subseries          | 713                  |
| Gender             | Male                 |
| Number of contacts | 4                    |
| Contact terminal   | Screw                |
| Upper temperature  | +85 °C               |
| Lower temperature  | -40 °C               |
| Protection degree  | IP67                 |
| Locking system     | Screw (M12-A)        |
| Mating cycles      | >50                  |
| Connector Diameter | 20.2 mm              |
| Cable outlet       | 2,5-3,5 mm           |
| Wire-section       | 0.75 mm <sup>2</sup> |

### Electrical parameters

# Product data sheet

## Binder connectoren

### Male cable connector



|                         |        |
|-------------------------|--------|
| Nominal current         | 4 A    |
| Nominal voltage         | 250 V  |
| Impuls voltage          | 2500 V |
| Max. contact resistance | 8 m?   |
| Pollution degree        | 3      |
| Overvoltage categorie   | II     |

## Material

|                     |                   |
|---------------------|-------------------|
| Material group      | III               |
| Material of insert  | PA                |
| Material of housing | PA                |
| Material of contact | CuZn (Brass)      |
| Plating             | CuSnZn (Optalloy) |