

# Product data sheet

## Binder connectoren


### Male cable connector



Lightgrey

99 9205 400 03

<https://www.ac-solutions.be/nl/product/99920540003>



## Specificaties

### General Characteristics

|                    |                      |
|--------------------|----------------------|
| Series             | Subminiature         |
| Subseries          | 620 Medical          |
| Gender             | Male                 |
| Number of contacts | 3                    |
| Contact terminal   | Solder               |
| Upper temperature  | +85 °C               |
| Lower temperature  | -25 °C               |
| Protection degree  | IP67                 |
| Locking system     | Snap-in              |
| Connector Diameter | 11.5 mm              |
| Cable outlet       | 3-5 mm               |
| Wire-section       | 0.25 mm <sup>2</sup> |

### Electrical parameters

|                 |       |
|-----------------|-------|
| Nominal current | 3 A   |
| Nominal voltage | 125 V |

# Product data sheet

## Binder connectoren

### Male cable connector



|                         |        |
|-------------------------|--------|
| Impuls voltage          | 1500 V |
| Max. contact resistance | 3 m?   |
| Pollution degree        | 2      |
| Overvoltage categorie   | II     |

## Material

|                     |                |
|---------------------|----------------|
| Material group      | II             |
| Material of insert  | PA (UL 94 V-0) |
| Material of housing | PA (UL 94 V-0) |
| Material of contact | CuZn (Brass)   |
| Plating             | Au (Gold)      |