

female contact, 0,75mm², gold 2µm, crimp, 10A, series CD



CDF2D 0.7

<https://www.ac-solutions.be/nl/product/cdf2d07>



Dominate All rights reserved

TIN PLATED	SILVER PLATED	JE GOLD PLATED	PART NUMBER	SPECIAL GOLD PLATED	HIGH NUMBER OF MATINGS	AWG	WIRE GAUGE	IDENTIFICATION	B	STAMPING LENGTH
DDFS 0.3	DDFA 0.3	DDFD 0.3	DDDF 0.3	DDFD 0.3	DDFD 0.3	0.80	0.14-0.37	26-22	1	
DDFS 0.5	DDFA 0.5	DDFD 0.5	DDDF 0.5	DDFD 0.5	DDFD 0.5	1.10	0.5	20	2	
DDFS 0.7	DDFA 0.7	DDFD 0.7	DDDF 0.7	DDFD 0.7	DDFD 0.7	1.30	0.75	18	3	
DDFS 1.0	DDFA 1.0	DDFD 1.0	DDDF 1.0	DDFD 1.0	DDFD 1.0	1.65	1	16	3	
DDFS 1.5	DDFA 1.5	DDFD 1.5	DDDF 1.5	DDFD 1.5	DDFD 1.5	1.6	1.5	16	4	
DDFS 2.5	DDFA 2.5	DDFD 2.5	DDDF 2.5	DDFD 2.5	DDFD 2.5	2.2	2.5	14	5	

23/02/18	Added new part numbers - HIGH NUMBER OF MATINGS (HNN)
23/02/17	Changed part numbers - CDF-25 was CDFD XX-1 and CDF-25 was CDFD XX-2
02/05/16	Added new part numbers - TIN PLATED
06/02/12	Added new part numbers - JE and SPECIAL GOLD PLATED

Dimensions in mm
Date 16/03/07
Sign: T. Tedeschi

CDF XX
Female crimp contact 10A

Scale
2:1

Specificaties

General characteristics

Connection type	Turned crimp
Contact type (gender)	Female
Min. Cross section	0.75 mm²
Max. Cross section	0.75 mm²
AWG size	18
Identification	?
Diameter male contact	1.6 mm
Wire strip length	8 mm

Electrical parameters

Max. rated current	10 A
--------------------	------

Material

Material contact	Copper alloy
Plating of contact	Gold