

female contact, 1,5mm², gold 2μm, crimp, 10A, series CD



CDF2D 1.5

<https://www.ac-solutions.be/nl/product/cdf2d15>



Demetral - rights reserved

TIN PLATED	SILVER PLATED	JE GOLD PLATED	PART NUMBER	SPECIAL GOLD PLATED	HIGH NUMBER OF MATINGS	ØA mm	WIRE GAUGE	IDENTIFICATION	B mm	STAMPING MARK
GDPS 0.3	GDPA 0.3	GDPO 0.3	GDPO 0.3	GDPO 0.3	GDPO 0.3	0.80	0.14-0.37 26-22	1		
GDPS 0.5	GDPA 0.5	GDPO 0.5	GDPO 0.5	GDPO 0.5	GDPO 0.5	1.00	0.25 20	2		
GDPS 0.7	GDPA 0.7	GDPO 0.7	GDPO 0.7	GDPO 0.7	GDPO 0.7	1.20	0.35 18	3		
GDPS 1.0	GDPA 1.0	GDPO 1.0	GDPO 1.0	GDPO 1.0	GDPO 1.0	1.45	1 16	3		
GDPS 1.5	GDPA 1.5	GDPO 1.5	GDPO 1.5	GDPO 1.5	GDPO 1.5	1.65	1.5 14	4		
GDPS 2.0	GDPA 2.0	GDPO 2.0	GDPO 2.0	GDPO 2.0	GDPO 2.0	2.2	2.5 14	5		

23/02/18	Added new part numbers - HIGH NUMBER OF MATINGS (HNM)
23/02/17	Changed part numbers - CDP-20 was CDPD XX-3 and CDP-25 was CDPD XX-2
02/05/16	Added new part numbers - TIN PLATED
06/02/12	Added new part numbers - JE and SPECIAL GOLD PLATED
Dimensions in mm	
Date	16/03/07
Sign.	T. Tedeschi

CDF XX
Female crimp contact 10A

Scale
2:1

Specificaties

General characteristics

Connection type	Turned crimp
Contact type (gender)	Female
Min. Cross section	1.5 mm²
Max. Cross section	1.5 mm²
AWG size	16
Identification	4
Diameter male contact	1.6 mm
Wire strip length	8 mm

Electrical parameters

Max. rated current	10 A
--------------------	------

Material

Material contact	Copper alloy
Plating of contact	Gold