

female contact, 0,5mm², gold, crimp, 10A, series CD





CDFD 0.5

<https://www.ac-solutions.be/nl/product/cdfd05>



Dimensions in mm
 Dimensions in inches

TIN PLATED	SILVER PLATED	JEL GOLD PLATED	PART NUMBER	NUMBER OF MATINGS	SPECIAL GOLD PLATED	HIGH NUMBER OF MATINGS	AWG	WIRE GAUGE	IDENTIFICATION	B (mm)	STAMPING MARK
GDPS 0.3	GDPA 0.3	GDPO 0.3	GDPO 0.3	GDPO 0.3	GDPO 0.3	GDPO 0.3	0.80	0.14-0.37	26-22	1	
GDPS 0.5	GDPA 0.5	GDPO 0.5	GDPO 0.5	GDPO 0.5	GDPO 0.5	GDPO 0.5	1.00	0.25	20	2	
GDPS 0.7	GDPA 0.7	GDPO 0.7	GDPO 0.7	GDPO 0.7	GDPO 0.7	GDPO 0.7	1.20	0.75	18	3	
GDPS 1.0	GDPA 1.0	GDPO 1.0	GDPO 1.0	GDPO 1.0	GDPO 1.0	GDPO 1.0	1.45	1	16	3	
GDPS 1.5	GDPA 1.5	GDPO 1.5	GDPO 1.5	GDPO 1.5	GDPO 1.5	GDPO 1.5	1.6	1.5	14	4	
GDPS 2.5	GDPA 2.5	GDPO 2.5	GDPO 2.5	GDPO 2.5	GDPO 2.5	GDPO 2.5	2.2	2.5	14	5	

23/02/18	Added new part numbers - HIGH NUMBER OF MATINGS (HNM)
23/02/17	Changed part numbers - GDPO 25 was GDPO XX-1 and GDPO 25 was GDPO XX-2
02/05/16	Added new part numbers - TIN PLATED
06/02/12	Added new part numbers - JEL and SPECIAL GOLD PLATED

Scale
2:1



Dimensions in mm

Date: 16/03/07

Sign: T. Tedeschi

CF XX

Female crimp contact 10A

Specificaties

General characteristics

Connection type	Turned crimp
Contact type (gender)	Female
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Min. Cross section	0.5 mm²
Max. Cross section	0.5 mm²
AWG size	20
Identification	2
Diameter male contact	1.6 mm
Wire strip length	8 mm

Electrical parameters

Max. rated current	10 A
--------------------	------

Material

Material contact	Copper alloy
Plating of contact	Gold