

male contact, 0,14-0,37mm², gold, crimp, 10A, series CD



CDMD 0.3

<https://www.ac-solutions.be/nl/product/cdmd03>



Dimensioni / Dimensions

TIN PLATED	SILVER PLATED	JE GOLD PLATED	PART NUMBER JE GOLD	NUMBER OF MATHES JE GOLD	SPECIAL GOLD PLATED	HIGH NUMBER OF MATHES JE GOLD	AWG mm	WIRE GAUGE mm ²	IDENTIFICATION	B mm	STAMPING MARK
CDMS 0.3	CDMA 0.3	CDMD 0.3	CDMD 0.3	CDMD 0.3	CDMD 0.3	CDMD 0.3	0.80	0.14-0.37	26-22	1	
CDMS 0.5	CDMA 0.5	CDMD 0.5	CDMD 0.5	CDMD 0.5	CDMD 0.5	CDMD 0.5	1.00	0.25	20	2	
CDMS 0.7	CDMA 0.7	CDMD 0.7	CDMD 0.7	CDMD 0.7	CDMD 0.7	CDMD 0.7	1.30	0.75	18	3	
CDMS 1.0	CDMA 1.0	CDMD 1.0	CDMD 1.0	CDMD 1.0	CDMD 1.0	CDMD 1.0	1.65	1	16	3	
CDMS 1.5	CDMA 1.5	CDMD 1.5	CDMD 1.5	CDMD 1.5	CDMD 1.5	CDMD 1.5	1.8	1.5	19	4	
CDMS 2.5	CDMA 2.5	CDMD 2.5	CDMD 2.5	CDMD 2.5	CDMD 2.5	CDMD 2.5	2.2	2.5	14	5	

23/02/18	Added new part numbers - HIGH NUMBER OF MATHES (HNM)
23/02/17	Changed part numbers - CDMD2 was CDMD XX-1 and CDMD5 was CDMD XX-2
02/05/16	Added new part numbers - TIN PLATED
06/02/12	Added new part numbers - JE and SPECIAL GOLD PLATED

Dimensions in mm
Date 16/03/07
Sign. T. Tedeschi

CDM XX
Male crimp contact 10A

Scale
2:1

Specificaties

General characteristics

Connection type	Turned crimp
Contact type (gender)	Male
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Min. Cross section	0.14 mm²
Max. Cross section	0.37 mm²
AWG size	26 - 22
Identification	1
Diameter male contact	1.6 mm
Wire strip length	8 mm

Electrical parameters

Max. rated current	10 A
--------------------	------

Material

Material contact	Copper alloy
Plating of contact	Gold