

# Product data sheet

## Ilme connectoren

hood, size 104.62, C-TYPE alu, 2 pegs, 1xPG42 side




CHO 48 L42


<https://www.ac-solutions.be/nl/product/cho48l42>



CHO L - MHO L - MFO L



CHV L - MHV L - MFV L



## Specificaties

### General characteristics

|                             |                               |
|-----------------------------|-------------------------------|
| Enclosure type              | Hood                          |
| Size                        | 104.62                        |
| Enclosure series            | C-TYPE                        |
| Closing type                | With 2 pegs                   |
| Locking mechanism           | Single locking lever          |
| Protection degree           | IP65 / IP66 / IP69            |
| Ambient lower temperature   | -40 °C                        |
| Ambient upper temperature   | 125 °C                        |
| Operation lower temperature | -40 °C                        |
| Operation upper temperature | 125 °C                        |
| Cable entry type            | side cable entry with adapter |
| Cable entry size            | Pg42                          |
| Position cable feed         | Side entry                    |
| Height                      | 107 mm                        |
| Width                       | 79 mm                         |
| Length                      | 121 mm                        |

## Material

# Product data sheet

## Ilme connectoren

hood, size 104.62, C-TYPE alu, 2 pegs, 1xPG42 side



|                                                            |                                                   |
|------------------------------------------------------------|---------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                          |
| Coating housing                                            | With epoxy-polyester thermosetting powder coating |
| Inflammability class of insulation material acc. with UL94 | V2                                                |