

Product data sheet



Ilme connectoren - CMCE 20 P + 4 P + PE

male insert, size 104.62, 10+2p+PE, crimp, 16A, 830V, no.11-20



CMCEM 10 N

<https://www.ac-solutions.be/nl/product/cmcem10n>



Specificaties

General characteristics

Product Type	Standard insert
Insert series	CMCE
Number of contacts	20 + 4 + PE (11-20)
Number of poles	20 + 4 + PE
Connection type	Crimp connection
Gender	Male
Size	104.62
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
AWG-range 1	26
AWG-range 2	12
Min. Cross section	0.14 mm ²
Max. Cross section	4 mm ²
Diameter male contact	2.5 mm
Pin numbers	11-20
Colour	Grey
Remark	To be ordered with CMCEM 10

Product data sheet

Ilme connectoren - CMCE 20 P + 4 P + PE

male insert, size 104.62, 10+2p+PE, crimp, 16A, 830V, no.11-20



Electrical parameters

Max. rated current	16 A
Nominal rated voltage	830 V
Rated surge voltage	8 kV
Pollution degree	3

Material

Material insert	Thermoplastic
Inflammability class of insulation material acc. with UL94	V0