

Product data sheet

Ilme connectoren - CME 16 P + 2 P + PE

male insert, size 104.27, 16+2p+PE, silver, screw, 16A, 690V




CMEM 16


<https://www.ac-solutions.be/nl/product/cmем16>



CMEM 16



CMEF 16



Specificaties

General characteristics

Product Type	Standard insert
Insert series	CME
Number of contacts	16 + 2 + PE
Number of poles	16
Connection type	Screw terminal connection
Gender	Male
Size	104.27
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
AWG-range 1	18
AWG-range 2	14
Min. Cross section without end sleeve	0.75 mm ²
Max. Cross section without end sleeve	2.5 mm ²
Min. Cross section	0.75 mm ²
Max. Cross section	2.5 mm ²
Colour	Grey
Extra information	With protective conductor, With wire protection

Product data sheet

Ilme connectoren - CME 16 P + 2 P + PE

male insert, size 104.27, 16+2p+PE, silver, screw, 16A, 690V



Electrical parameters

Max. rated current	16 A
Nominal rated voltage	400/690 V
Over voltage category	III
Rated surge voltage	6 kV
Pollution degree	3

Material

Material insert	Thermoplastic
Material contact	Copper alloy
Plating of contact	Silver
Inflammability class of insulation material acc. with UL94	V0