

Product data sheet



Ilme connectoren - CT 24 P + PE

female insert, size 104.27, 24p+PE, silver, screw, 16A, 400V, left



CTF 24 L

<https://www.ac-solutions.be/nl/product/ctf24l>



Specificaties

General characteristics

Product Type	Standard insert
Insert series	CT
Number of contacts	24 + PE
Number of poles	24
Connection type	Screw terminal connection
Gender	Female
Size	104.27
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
AWG-range 1	18
AWG-range 2	14
Min. Cross section without end sleeve	0.75 mm ²
Max. Cross section without end sleeve	2.5 mm ²
Min. Cross section	0.75 mm ²
Max. Cross section	2.5 mm ²
Colour	Grey
Extra information	Modular version, With protective conductor, With wire protection

Product data sheet

Ilme connectoren - CT 24 P + PE

female insert, size 104.27, 24p+PE, silver, screw, 16A, 400V, left



Remark	Only for bulkhead mounted housings and BIG hoods
--------	--

Electrical parameters

Max. rated current	16 A
Nominal rated voltage	400 V
Over voltage category	III
Rated surge voltage	4 kV
Pollution degree	2

Material

Material insert	Thermoplastic
Material contact	Copper alloy
Plating of contact	Silver
Inflammability class of insulation material acc. with UL94	V0