

Product data sheet



Ilme connectoren - CTS 40 P + PE

male insert, size 77.27, 40p+PE, silver, spring, 10A, 250V, left



CTSM 40 L

<https://www.ac-solutions.be/nl/product/ctsm40l>



Specificaties

General characteristics

Product Type	Standard insert
Insert series	CTS
Number of contacts	40 + PE
Number of poles	40
Connection type	Spring terminal connection
Gender	Male
Size	77.27
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
AWG-range 1	26
AWG-range 2	14
Min. Cross section with end sleeve	0.14 mm ²
Max. Cross section with end sleeve	1 mm ²
Min. Cross section without end sleeve	0.14 mm ²
Max. Cross section without end sleeve	2.5 mm ²
Min. Cross section	0.14 mm ²
Max. Cross section	2.5 mm ²

Product data sheet

Ilme connectoren - CTS 40 P + PE

male insert, size 77.27, 40p+PE, silver, spring, 10A, 250V, left



Colour	Grey
Extra information	With protective conductor,With wire protection
Remark	Only for bulkhead mounted housings

Electrical parameters

Max. rated current	10 A
Nominal rated voltage	250 V
Over voltage category	III
Rated surge voltage	4 kV
Pollution degree	3

Material

Material insert	Thermoplastic
Material contact	Copper alloy
Plating of contact	Silver
Inflammability class of insulation material acc. with UL94	V0