

Product data sheet


Ilme connectoren - CX RY 4 P + PE

male insert, size 77.27, 4p+PE, screw, 80A, 830V, 180°



CXM 4/0 RY

<https://www.ac-solutions.be/nl/product/cxm40ry>



Specificaties

General characteristics

Product Type	Standard insert
Insert series	CX RY
Number of contacts	4 + PE
Number of poles	4
Connection type	Screw terminal connection
Gender	Male
Size	77.27
Operation lower temperature	-40 °C
Operation upper temperature	180 °C
AWG-range 1	12
AWG-range 2	6
Min. Cross section with end sleeve	4 mm ²
Max. Cross section with end sleeve	16 mm ²
Min. Cross section	4 mm ²
Max. Cross section	16 mm ²
Colour	Brown
Extra information	With protective conductor

Product data sheet

Ilme connectoren - CX RY 4 P + PE

male insert, size 77.27, 4p+PE, screw, 80A, 830V, 180°



Electrical parameters

Max. rated current	80 A
Nominal rated voltage	830 V
Over voltage category	IV
Rated surge voltage	8 kV
Pollution degree	3

Material

Material insert	Thermoplastic
Material contact	Copper alloy
Plating of contact	Silver
Inflammability class of insulation material acc. with UL94	V0