# Product data sheet

## Higo connectoren - L1019D

### Male cable connector

L1019DG P 00 BX 1000
https://www.ac-solutions.be/nl/product/l1019dgp00bx1000




## Specificaties

### General Characteristics

| | |
|---|---|
| **Number of contacts** | 10 (3+7) |
| **Connector shape** | Plug |
| **Gender** | Male |
| **Color** | Black |
| **Upper temperature** | 80 °C |
| **Lower temperature** | -25 °C |
| **Protection degree** | IP67 |
| **Mating cycles (times)** | 200 Times |
| **Connector diameter** | 19 mm |
| **Fitting length** | 114 mm |
| **Cable Length** | 1000 mm |
| **Cable diameter** | 11 mm |
| **Wire section** | 3 x 5,3 + 7 x 0,14 |
| **Remark** | *Rated current: 45A / 2A, 2 power pin loaded 40A / 2A, 3 power pin loaded Other cable length/type on request |

# Product data sheet

## Higo connectoren - L1019D

### Male cable connector

## Electrical Parameters

| | |
|---|---|
| **Rated current** | *45 / 2 |
| **Rated voltage** | 48 V AC / 60 V DC |
| **Max. insulation resistance (M?)** | ?20 M? |
| **Max. contact resistance (M?)** | ?10 m? |

## Material

| | |
|---|---|
| **Material jacket** | PVC |
| **Insulation wire** | FEP |
| **Material of contact** | Copper alloy |
| **Contact plating** | Gold plated |