

# Product data sheet



## Ilme connectoren

surface mounting housing, high, size 77.27, E-Xtreme alu, 2 levers, 2xM32 side



M7APE 16.232

<https://www.ac-solutions.be/nl/product/m7ape16232>



## Specificaties

### General characteristics

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| Enclosure type              | Surface mounting housing                                        |
| Size                        | 77.27                                                           |
| Enclosure series            | E-Xtreme® V-TYPE                                                |
| Closing type                | With 2 levers                                                   |
| Locking mechanism           | Double locking levers                                           |
| Protection degree           | IP66 / IP67 / IP69                                              |
| Ambient lower temperature   | -40 °C                                                          |
| Ambient upper temperature   | 125 °C                                                          |
| Operation lower temperature | -40 °C                                                          |
| Operation upper temperature | 125 °C                                                          |
| Cable entry type            | side cable entry                                                |
| Cable entry size            | M32 x 2                                                         |
| Position cable feed         | Side entry                                                      |
| Height                      | 77 mm                                                           |
| Width                       | 57 mm                                                           |
| Length                      | 105 mm                                                          |
| Remark                      | FKM gasket (-40°C...+180°C) or silicone gasket (-60°C...+180°C) |

# Product data sheet

## Ilme connectoren

surface mounting housing, high, size 77.27, E-Xtreme alu, 2 levers, 2xM32 side



### Material

|                                                            |                                                   |
|------------------------------------------------------------|---------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                          |
| Coating housing                                            | With epoxy-polyester thermosetting powder coating |
| Inflammability class of insulation material acc. with UL94 | V2                                                |