

Product data sheet


Ilme connectoren

surface mounting housing, high, size 77.27, C-TYPE alu, 4 pegs, 2xM32 side, cover plastic




MAP 16 CP232


<https://www.ac-solutions.be/nl/product/map16cp232>



CHP CAP - MHP MAP



CHP CS/CP CAP CS/CP - MHP CS/CP MAP CS/CP



	A
CHP / MHP	63
CAP / MAP	77
CHP CS / MHP CS	63
CAP CS / MAP CS	77
CHP CP / MHP CP	63
CAP CP / MAP CP	77

Specificaties

General characteristics

Enclosure type	Surface mounting housing
Size	77.27
Enclosure series	C-TYPE
Closing type	With 4 pegs
Locking mechanism	Double locking levers
Protection degree	IP65
Ambient lower temperature	-40 °C
Ambient upper temperature	125 °C
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Cable entry type	side cable entry
Cable entry size	M32 x 2
Position cable feed	Two-sided
Height	81 mm
Width	57 mm
Length	117 mm
Remark	May be combined with enclosures: CHO 16 X, CAO 16 X, CHV 16 X, CAV 16 X, MHO 16 X, MAO 16 X, MHV 16 X, MAV 16 X

Product data sheet

Ilme connectoren

surface mounting housing, high, size 77.27, C-TYPE alu, 4 pegs, 2xM32 side, cover plastic



Material

Material housing	Die cast aluminium alloy
Coating housing	With epoxy-polyester thermosetting powder coating
Inflammability class of insulation material acc. with UL94	V2
Extra information	Corrosion resistant,UV resistant,With hinged lid,With interlocking device