

# Product data sheet


## Ilme connectoren

hood, size 104.27, IP68 E-Xtreme alu, screw locking, 3xM25 top



MGVE 24.325

<https://www.ac-solutions.be/nl/product/mgve24325>



## Specificaties

### General characteristics

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| Enclosure type              | Hood                                                            |
| Size                        | 104.27                                                          |
| Enclosure series            | E-Xtreme® IP68                                                  |
| Closing type                | With 2 screws                                                   |
| Locking mechanism           | With 2 screws                                                   |
| Protection degree           | IP66 / IP68 / IP69                                              |
| Ambient lower temperature   | -40 °C                                                          |
| Ambient upper temperature   | 125 °C                                                          |
| Operation lower temperature | -40 °C                                                          |
| Operation upper temperature | 125 °C                                                          |
| Cable entry type            | top cable entry                                                 |
| Cable entry size            | M25 x 3                                                         |
| Position cable feed         | Top entry                                                       |
| Height                      | 111 mm                                                          |
| Width                       | 58 mm                                                           |
| Length                      | 193 mm                                                          |
| Remark                      | FKM gasket (-40°C...+180°C) or silicone gasket (-60°C...+180°C) |

# Product data sheet

## Ilme connectoren

hood, size 104.27, IP68 E-Xtreme alu, screw locking, 3xM25 top



### Material

|                                                            |                                                   |
|------------------------------------------------------------|---------------------------------------------------|
| Material housing                                           | Die cast aluminium alloy                          |
| Coating housing                                            | With epoxy-polyester thermosetting powder coating |
| Inflammability class of insulation material acc. with UL94 | V2                                                |