

Product data sheet

Ilme connectoren

hood, high, size 66.16, IL-BRID alu, 2 pegs, 2xM20 top, no adaptor




MZFV 25 L220


<https://www.ac-solutions.be/nl/product/mzfv25l220>



CZAV L2 - (MZAV L2) - [MZFV L2]



CAV - MAV - MFV



Specificaties

General characteristics

Enclosure type	Hood
Size	66.16
Enclosure series	IL-BRID
Closing type	With 2 pegs
Locking mechanism	Single locking lever
Protection degree	IP66 / IP67 / IP69
Ambient lower temperature	-40 °C
Ambient upper temperature	125 °C
Operation lower temperature	-40 °C
Operation upper temperature	125 °C
Cable entry type	double top cable entry
Cable entry size	M20 x 2
Position cable feed	Top entry
Height	70.5 mm
Width	16 mm
Length	66 mm
Remark	Enclosure without adaptor, threaded on the body, to be used only with a complete cable gland

Product data sheet

Ilme connectoren

hood, high, size 66.16, IL-BRID alu, 2 pegs, 2xM20 top, no adaptor



Material

Material housing	Die cast aluminium alloy
Coating housing	With epoxy-polyester powder coating
Inflammability class of insulation material acc. with UL94	V2
Extra information	Corrosion resistant,UV resistant,With interlocking device